

Amendments to the Claims:

The following listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Currently Amended) A manufacturing method for an organic electro-luminescent device, comprising:

forming light emitting layers by discharging, above a substrate, at least two compositions, each including ~~at least one~~two or more organic electro-luminescent material; and

ordering discharging said compositions above the substrate starting with a composition which has a fewest number of organic electro-luminescent materials.

2. (Currently Amended) A manufacturing method for an organic electro-luminescent device, comprising:

forming light emitting layers by discharging, above a substrate, at least two compositions, each including ~~at least one~~two or more organic electro-luminescent material; and

when discharging compositions which has a same number of organic electro-luminescent materials, ordering discharging said compositions above the substrate starting with a composition which is most difficult to be phase separated after the layer is formed.

3. (Previously Presented) The manufacturing method for an organic electro-luminescent device according to claim 1, further including the step of, during two continuous cycles of discharging said compositions, performing the subsequent discharging of a composition after the composition discharged in a first cycle are dried.

4. (Previously Presented) The manufacturing method for an organic electro-luminescent device according to claim 3, further including the steps of, prior to said step for forming a light emitting layer, forming pixel electrodes corresponding to a plurality of pixel

regions and banks separating said pixel regions above said substrate; forming a hole injection/transport layer above said pixel electrodes of said plurality of pixel regions; and after said process for forming a light emitting layer, forming a counter electrode above said light emitting layer.

5. (Withdrawn) An organic electro-luminescent device manufactured by the manufacturing method according to claim 1.

6. (Withdrawn) An electronic equipment, comprising:
the organic electro-luminescent device according to claim 5.

7. (Previously Presented) The manufacturing method for an organic electro-luminescent device according to claim 2, further including the step of, during two continuous cycles of discharging said compositions, performing the subsequent discharging of a composition after the composition discharged in a first cycle are dried.

8. (Withdrawn) An organic electro-luminescent device manufactured by the manufacturing method according to claim 2.

9. (Previously Presented) The manufacturing method for an organic electro-luminescent device according to claim 7, further including the steps of, prior to said step for forming a light emitting layer, forming pixel electrodes corresponding to a plurality of pixel regions and banks separating said pixel regions above said substrate; forming a hole injection/transport layer above said pixel electrodes of said plurality of pixel regions; and after said process for forming a light emitting layer, forming a counter electrode above said light emitting layer.

10. (Withdrawn) An electronic equipment, comprising:
the organic electro-luminescent device according to claim 8.